

McHale

991L

Round Bale Wrapper
991L-LB-LBER-TBER SERIES



The Professional Choice

“dependable performance”

For thousands of contractors and owner operators McHale is the name for Round Bale Wrapping - A perfect blend of tried and tested technology with solid construction and dependable performance. Depending on your requirements the 991L series can be supplied with practical features including the hydraulic cut and tie system and the efficient 750mm film dispenser unit which maximises film usage, all which can be simply controlled with the touch of a button or a remote control. Like all McHale Balewrappers, the high output 911L Series will give you a tightly wrapped bale that increases feed quality and contains the natural juices for greater nutritional value while giving increased environmental protection.

remote control

When used with an independent power pack and an infra red remote control, this machine will eliminate the need for a second tractor and operator. While one bale is being wrapped the operator can stack the last completed bale ready to complete the cycle. This economical and efficient method of bale wrapping can reduce operating costs by up to 50% while keeping the handling of the wrapped bales to a minimum.



cut & tie

The McHale hydraulically operated Cut and Tie System cuts and holds the film in position ready to wrap the next bale. This time saving device eliminates the need to manually reattach the film.

Uniquely designed, this system works reliably and consistently in all weather conditions.



Quick fit dispenser



Reloading new roll



Locking in new roll







McHale



McHale 991 TBER

991_L

Round Bale Wrapper

991L-LB-LBER-TBER SERIES

DISTRIBUTED BY

Technical Data

| Linkage Model [Round] | 991L, 991LB, 991LBER |
|--------------------------------|---|
| Total Length | 2.8m (9'2") |
| Transport Width | 1.65m (5'5") |
| Height to top of rollers | 0.83m (2'9") |
| Total Height | 1.94m (6'4") |
| Min oil req. litres per minute | 18 @ 150 bar |
| Max bale weight | 1200kg. (2646 lbs) |
| Lift Capacity @ 170 bar | 1100 kg. (2425 lbs.) |
| Weight (unladen) | 800 kg. (1764 lbs) |
| Working speed-table (up to) | 30 rotations/min |
| Electrical requirements | 12v/dc 7 pin (991L) 12v/from battery (991LBER) |
| Driver Control | 3 Bank Valve & monitor(991LB) Elec. box & remote (991LBER) |
| Film Holders | 2 |
| Dispenser - Aluminium 70/55% | 750/500mm |
| Protection Mechanism | Shear bolt/roll pin |
| Greasing Points | 11 |

| Equipment on each model | 991L | 991LB | 991LBER |
|--|------|-------|---------|
| 750/500 Dispenser | ✓ | ✓ | ✓ |
| 2 film holders | ✓ | ✓ | ✓ |
| Bale Support Bobbins | ✓ | ✓ | ✓ |
| Quick Hitch system | ✓ | ✓ | ✓ |
| Cut & Tie | ✓ | ✓ | ✓ |
| Bale wrap monitor | ✓ | ✓ | ✓ |
| Fully auto/remote and manual over-ride | ✓ | ✓ | ✓ |

Optional Equipment

55% Stretch Gears

| Export Packaging Dimensions | per stack of 2 |
|-----------------------------|----------------|
| Length | 3.27m (10'8") |
| Width | 2.28m (7'6") |
| Height | 2.30m (7'7") |

Due to the continuing policy of product improvement, we reserve the right to alter specification and construction without notice



McHale

McHale Engineering Limited,
Castlebar Rd. Ballinrobe, Co. Mayo, Ireland.

Tel: 353 94 9520300
Fax: 353 94 9520356

Email: sales@mchale.net
Web: www.mchale.net