



dropside, double-axle TRAILERS

D-606, D-608, D-610, D-612
D-614

- light reliable design
- spring suspended system
- speed of up to 40 km/h
- possibility of coupling additional double-axle trailer
- central opening and closing of sides
- width to fit two europalettes

NOVELTY!



The D-606, D-608, D-610, D-612, D-614 double-axle agricultural trailers are intended for transporting agricultural produce. Sideboards and backside with centrally controlled opening/closing system ensure quick unloading. Adjustable gate in the backside makes it possible to control the flow of loose materials. The 2,4 m width of the loading platform allows them to be successfully used for transporing of euro-pallets. The trailers are provided with the rear hitch and couplings for attaching the second trailer. Upon request, they can be provided with a frame and canvas. The trailers are fully adapted to use on public roads with the speed of 40 km/h. Their are solid design guarantees failure-free operation for many years.

	D-606	D-608	D-610	D-612	D-614
Load capacity, t	up to 6	up to 8	up to 10	up to 12	up to 14
Min. tractor horsepower, kW/HP	35[47]	45[61]	55[75]	65[88]	80[109]
Platform area, m²	10,70		12,3		
Capacity of the main load-body, m ³	5,35 [10,7 with extension]		6,15 [12,3 with exten.]	7,35 [14,7with exten.]	7,35 [17,1 with exten.]
Overall dimensions:					
length x width x height, mm	6600/2550/2120	6600/2550/2160÷2370	7130/2550/2360÷2560	7130/2550/2560÷2760	7130/2550/2760÷2860
Internal dimensions of the load body:					
length x width x height/exten., mm	4440 x 2410 x 500/500	5100x2410x500/500		5100 x 2410 x 600/600	5100 x 2410 x 600/800
Platform height over the ground, mm	1120	1160÷1330	1330÷1530	1330÷1530	1330÷1430
Wheelbase, mm	1800		1850		
Suspension			parabolic springs		
Tire size	400/60-15,5 14PR		385/65-R22,5 [15R22,5]		
Unloading system	three-sided				
Body type	dropside				
Standard equipment	manual rear hitch, hydraulic, pneumatic and electric connections to second trailer				
Options	extension, balcony, canvas with the frame, spare wheel, wheel chocks, fenders, hydraulic brakes,				
	tools box, LED lights, rear, side chute, rear hitch automatic,				
	painting to customer order				
Wheels:	14.0/65-16 14PR	14.0/65-16 14PR	425/65-R22,5, 445/50-R22,5		455/40-R22,5
		12,5/80-18 14PR	455/40-R22,5, 500/45-R22,5		
		15,0/70-18 14PR	500/60-R22,5		



Toolbox and the water tank



Hydraulic, pneumatic and electric connection to second trailer



loading capacity 6 -14 t

dropside, single-axle TRAILERS

T-040

functional design
light, robust and safe
improves traction properties
of a tractor

	T-040
Load capacity, t	3,5
Trailer weight, kg	1230
Min. tractor horsepower, kW/HP	35/48
Platform area, m	6,39
Capacity of the main load-carrying body, m	3,2
Capacity of the body with extension sides, m	5,1
Overall dimensions without extension sides:	
length x width x height, mm	4480 x 2235 x 1445
Internal dimensions of the load-carrying body:	
length x width x height, mm	3110x2055x500
Height with extension sides, mm	800
Tire size	11,5/80-15,3 12PR
Braking system	pneumatic, double-line
Unloading	three-sided tipping
Body type	dropside
Driving speed, km/h	40
Load on tractor hitch, kN/kg	7,2 [740]
Standard equipment	300 mm extension sides
Options	400/60 -15,5 12 PR tyres hydraulic brakes

The T-040 single-axle agricultural trailer is intended for transporting agricultural produce. It was designed to be combined with the tractor's lower transport hitch. A low positioned floor of the load carrying body enables non-mechanized loading and unloading. Adjustable chute in the backside allows a controlled flow of loose materials. The T-040 trailer has three-sided unloading. A single-axle suspension system guarantees good traction properties of a set in different ground conditions. The trailer is fully suited to road transport. It is equipped with the pneumatic braking and lighting systems.



T-042

T-080/2A

T-042, T-080/2A
functional design
light, durable and safe
excellent traction
characteristics of a set
central opening and closing
of sides

	T-042	T-080/2A
Load capacity, t	7	10
Trailer weight, kg	2170	2732
Min. tractor horsepower, kW/HP	50/68	70/95
Platform area, m	7,86	10,20
Capacity of the body with ext. sides, m	7,86	12,30
Overall dimensions with extension sides:		
length x width x height, mm	5275 x 2310 x 1520	5860 x 2500 x 2210
Internat dim. of the load-carrying body:		
length x width x height, mm	3705 x 2110 x [500 +500]	4410 x 2320 x [600+600]
Height with extension sides, mm	1000	1200
Tire size	11,5/80-15,3 10 PR	400/60-15,5 14 PR
Braking system	pneumatic, double-line	
Unloading	three-sided	
Driving speed, km/h	40	25 (40 for T-080/2A)
Load on tractor hitch, kN/kg	1482 [1500]	18,32[1900]
Option	400/60 x 15,5 14PR tires	—
	hydraulic brakes, spare wheel	



diameter of the drawbars eye
50mm (40mm in option)

The T-042 and T-080/2 single-axle agricultural trailers are intended for transporting agricultural produce. They were designed to be combined with tractors equipped with a lower transport hitch. A low positioned floor of the load carrying body enables non-mechanized loading and unloading. The adjustable gate in the backside makes it possible to control the flow of loose material. The trailers have three-sided unloading. A single-axle tandem-type suspension system significantly improves traction characteristics of a tractor. The trailers are fully suited to road transport. There are equipped with the pneumatic braking and lighting systems.

monocoque, single-axle TRAILERS T-083/A

- robust design
- tandem suspension system ensuring good traction
- characteristics of a set
- easy maneuvering of the whole set

The T-083 single-axle trailers with backwards unloading system are intended for transporting agricultural produce. They were designed to be combined with tractors equipped with a lower transport hitch. Adjustable chute in the tail gate allows a controlled flow of loose materials. The monocoque body design ensures good tightness. The tandem suspension system significantly improves traction properties of a tractor. The trailers are fully suited to road transport. There are equipped with the pneumatic braking and lighting systems.



T-083/A

Load capacity, t	10
Trailer weight, kg	2720
Min. tractor horsepower, kW/HP	70 / 95
Platform area, m	9,90
Capacity of the body with side extensions, m	10,86
Overall dimensions without extension sides:	
length x width x height, mm	6015 x 2440 x 1800
Internal dimensions of the load-carrying body:	
length x width x height, mm	4510 x 2200 x 1100
Height with side extensions, mm	1100
Tire size	400-60 R15
Braking system	pneumatic, double-line
Unloading	backwards
Body type	monocoque
Driving speed, km/h	40
Load on tractor hitch, kN[kg]	17,84 [1820]
Standard equipment	extension 400 mm
Options	manual rear hitch, hydraulic, pneumatic and electric connections to second trailer
	spare wheel, fenders, wheel wedges, hydraulic support,
	hydraulic brakes, balcony, canvas with the frame
	painting to customer order

loading capacity 10 t

NOVELTY!

monocoque, single-axle CONSTRUCTION TRAILERS T-623, T-623/2

- robust design
- suitable for high point pressures
(HARDOX 400 metal sheet)
- suspension system ensuring
excellent
- traction characteristics of a set

	T-623	T-623/2
Load capacity, t	12	14
Trailer weight, kg	4 150	4 620
Min. tractor horsepower, kW/HP	70/95	
Platform area, m	10,20	12,50
Capacity of the main body, m	7,02	10,00
Overall dim. without ext. sides:		
length x width x height, mm	5,86 x 2,40 x 0,75	6,82 x 2,54 x 0,85
Internal dim. of the body:		
length x width x height, mm	4,23 x 2,40 x 0,69	5,20 x 2,40 x 0,80
Tire size	505/50 R17 146G	385/65 R 22,5
Braking system	pneumatic, double-line	
Unloading	backwards	
Body type	monocoque	
Driving speed, km/h	40	
Load on tractor hitch, kN[kg]	24 [2450]	28[2850]
Options	hydraulic brakes, extensions 1000 mm	



T-041K/N

T-041K/N

Load capacity, t	10
Trailer weight, kg	3 000
Min. tractor horsepower, kW/HP	70/95
Platform area, m	8,80
Capacity of the main body, m	4,80
Overall dim. without ext. sides:	
length x width x height, mm	5,27 x 2,35 x 0,65
Internal dim. of the body:	
length x width x height, mm	3,47 x 2,35 x 0,59
Tire size	505/50 R17 146G
Braking system	pneumatic, double-line
Unloading	backwards
Body type	monocoque
Driving speed, km/h	40
Load on tractor hitch, kN[kg]	24 [2450]
Options:	hydraulic brakes extensions 1000 mm



loading capacity 10 t